

TECHNICAL SPECIFICATIONS

MODEL	UNO-20FSE / i20NBV Brush Assist
DIMENSIONS L	55.7 in / 1,415 mm
DIMENSIONS W	22 in / 560 mm
DIMENSIONS H	44.9 in / 1,140 mm
WEIGHT	210 lbs / 95 Kg
WEIGHT WITH BATTERIES	410 lbs / 185 Kg
RECOVERY TANK CAPACITY	17.2 Gal / 65 L
SOLUTION TANK CAPACITY	15.9 Gal / 60 L
SQUEEGEE WIDTH	30 in / 762 mm
CLEANING PATH WIDTH	20 in / 500 mm (Disk)
PRODUCTIVITY RATE	19,375 ft ² / 1,800 m ² h
DRIVE SYSTEM	Brush Assisted
TRAVEL SPEED, MAXIMUM	N/A
MINIMUM AISLE TURN	63 in / 1,600 mm
PAD/BRUSH PRESSURE	65 lbs / 30 Kg Min
SOLUTION FLOW RATE	0 ~ 0.37 Gal / Min 0 ~ 1,400 ml / Min
BRUSH MOTOR	0.75hp / 0.55KW 180 RPM
VIBRATIONS @ CONTROLS	N/A
VACUUM MOTOR	0.54hp / 0.4KW
WATER LIFT - AIR FLOW	45 in / 1,143 mm
BATTERIES	2-12, 105AH @ 20 hr
RUN TIME PER CHARGE	3 Hours
VOLTAGE DC	24V
DECIBEL RATE AT OPERATOR'S EAR, INDOORS	68dB(A)
GRADE LEVEL, MAX	5% (3°)