



# Advancing Restoration

## LGR 7000XLi

### TRUE LGR Performance - Unleashed!

Breaking the performance barriers as the new category leader, the LGR 7000XLi removes more water than any other dehumidifier in its category!

### Product Features

- Advanced Crossflow Technology maximizes efficiency even in low grain environments. Ensures best performance across range.
- Self-monitoring system. Built-in sensors monitor performance parameters allowing for automatic fan speed adjustments.
- Built-in humidistat and plain-English control panel messages
- Sealed large-capacity pump basin – more than enough to handle the water from an unintentional defrost that might occur after a power outage or other unexpected shut-down.
- Ergonomic design. Handle 2 in. taller for easier use on stairs, folds down for storage. Integrated cord and hose storage.
- Versatile application – standard 12 in. ductable outlet.
- Legendary rotomolded housing – practically indestructible – resists dents and dings – stackable for storage – saves room in warehouse.
- If power is interrupted during operation, the unit will automatically restart when power is restored. (115V models only.)



Item #F412

\$2,350 Suggested List U.S. Funds

### Product Specifications

Model	LGR 7000XLi
Power	8.3 amps, 115V
Water removal AHAM (80°F/60%RH)	130 pints   61.5 liters / day
Max. water removal at saturation	235 pints   111 liters / day
Water removal LGR	40% more than competitive units
Operating range	33° – 100°F 1° – 38°C
Process air (max.)	325 CFM   552 CMH. Floor-level outlet.
Filter type	3M HAF filter 24 pack F368 (same as DrizAir 1200)
Dimensions (H × W × D)	33.5 × 20 × 20 in.   85 × 51 × 51 cm
Use weight	107 lbs.   49 kg
Drain hose	40 ft.   12.2 m
Power cord	25 ft.   7.6 m
Construction	Rotomolded polyethylene shell.