

MATERIAL SAFETY DATA SHEET

Misty Vandalism Mark Remover

Section 1: PRODUCT AND COMPANY IDENTIFICATION

Product Name: Misty Vandalism Mark Remover
Product Number: A00178
Product Use: Cleaner.
Manufacturer/Supplier: Amrep, Inc.
990 Industrial Park Drive
Marietta, GA 30062
Phone Number: (770) 422-2071 (Mon - Fri / 8am - 5pm ET)
D.O.T. Emergency Phone: CHEM TEL (800) 255-3924
INTERNATIONAL: +01-813-248-0584
Date of Preparation: November 12, 2007 **Revision #:** 1.0

Section 2: HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

HMIS: See Section 15

DANGER

EXTREMELY FLAMMABLE. HARMFUL BY INHALATION. MAY CAUSE EYE IRRITATION. MAY CAUSE SKIN IRRITATION. CONTENTS UNDER PRESSURE. CONTAINER MAY EXPLODE IF HEATED.

Potential Health Effects: See Section 11 for more information.

Likely Routes of Exposure: Skin contact, eye contact, inhalation, and ingestion.

Eye: May cause eye irritation.
Skin: May cause skin irritation.
Ingestion: Not a normal route of exposure. Harmful: may cause lung damage if swallowed.
Inhalation: Harmful by inhalation. May cause respiratory tract irritation. May cause asphyxiation. This product may be aspirated into the lungs and cause chemical pneumonitis.

Chronic Effects: Prolonged or repeated contact may dry skin and cause irritation.

Signs and Symptoms: Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. Handling can cause dry skin. Vapours may cause drowsiness and dizziness.

Medical Conditions Aggravated By Exposure: Asthma. Allergies.

Target Organs: Skin, eyes, gastrointestinal tract, respiratory system.

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Potential Environmental Effects: May cause long-term adverse effects in the aquatic environment. See Section 12 for more information.

Section 3: COMPOSITION / INFORMATION ON INGREDIENTS

Ingredient	CAS #	Wt. %
Acetone	67-64-1	30 - 60
Toluene	108-88-3	10 - 30
Isobutane	75-28-5	5 - 10
Ethylene glycol monobutyl ether	111-76-2	5 - 10
Methyl ethyl ketone	78-93-3	6 - 10
Propane	74-98-6	3 - 7

MATERIAL SAFETY DATA SHEET

Misty Vandalism Mark Remover

Section 4: FIRST AID MEASURES

Eye Contact: In case of contact, immediately flush eyes with plenty of water. If easy to do, remove contact lenses, if worn.

Skin Contact: In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Call a physician if irritation develops and persists.

Inhalation: If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen.

Ingestion: If swallowed, do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person.

General Advice: In case of accident or if you feel unwell, seek medical advice immediately (show the label or MSDS where possible).

Note to Physicians: Symptoms may not appear immediately.

Section 5: FIRE FIGHTING MEASURES

Flammability: Flammable by WHMIS/OSHA criteria.

Means of Extinction:

Suitable Extinguishing Media: Powder, water spray, foam, carbon dioxide.

Unsuitable Extinguishing Media: Not available.

Products of Combustion: May include, and are not limited to: oxides of carbon.

Explosion Data:

Sensitivity to Mechanical Impact: Not available.

Sensitivity to Static Discharge: Not available.

Protection of Firefighters: Containers may explode when heated. Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).

Section 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions: Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Eliminate sources of ignition. Ruptured cylinders may rocket.

Environmental Precautions: Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). This material is a water pollutant. Keep out of drains, sewers, ditches, and waterways. Minimize use of water to prevent environmental contamination.

Methods for Containment: Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).

Methods for Clean-Up: Vacuum or sweep material and place in a disposal container. Allow gas to dissipate harmlessly into the atmosphere.

Other Information: Not available.

MATERIAL SAFETY DATA SHEET

Misty Vandalism Mark Remover

Section 7: HANDLING AND STORAGE

Handling:

Keep away from sources of ignition. - No smoking. Avoid contact with skin and eyes. Do not swallow. Do not breathe gas/fumes/vapor/spray. Use only in well-ventilated areas. Handle and open container with care. When using, do not eat or drink. Wash hands before eating, drinking, or smoking.

Storage:

Keep out of the reach of children. Keep container in a well-ventilated place. Do not store at temperatures above 49°C / 120°F.

Section 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

Ingredient	Exposure Limits	
	OSHA-PEL	ACGIH-TLV
Acetone	1000 ppm	500 ppm
Toluene	200 ppm	50 ppm
Isobutane	Not available.	Not available.
Ethylene glycol monobutyl ether	50 ppm	20 ppm
Methyl ethyl ketone	200 ppm	200 ppm
Propane	1000 ppm	1000 ppm

Engineering Controls: Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits.

Personal Protective Equipment:

HMIS: See Section 15

Eye/Face Protection: Wear eye/face protection.

Hand Protection: Wear suitable gloves.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: In case of insufficient ventilation, wear suitable respiratory equipment.

General Hygiene Considerations: Handle according to established industrial hygiene and safety practices.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Clear.
Color:	Colorless.
Odour:	Aromatic.
Odour Threshold:	Not available.
Physical State:	Gas/Pressurized Liquid.
pH:	Not applicable.
Viscosity:	Not available.
Freezing Point:	Not available.
Boiling Point:	Not available.
Flash Point:	Not available.
Evaporation Rate:	Not available.

MATERIAL SAFETY DATA SHEET

Misty Vandalism Mark Remover

Lower Flammability Limit:	Not available.
Upper Flammability Limit:	Not available.
Vapor Pressure:	Not available.
Vapor Density:	Not available.
Specific Gravity:	0.810 (Concentrate only)
Solubility in Water:	Partial.
Coefficient of Water/Oil Distribution:	Not available.
Auto-ignition Temperature:	Not available.
Percent Volatile, wt. %:	Not available.
VOC content, wt. %:	49.0% (US federal/CARB/OTC/LADCO)

Section 10: STABILITY AND REACTIVITY

Stability: Stable under normal storage conditions. Contents under pressure. Container may explode if heated. Do not puncture. Do not burn. Keep in a cool place.

Conditions of Reactivity: Heat. Incompatible materials.

Incompatible Materials: Oxidizers. Acids.

Hazardous Decomposition Products: May include, and are not limited to: oxides of carbon.

Possibility of Hazardous Reactions: No dangerous reaction known under conditions of normal use.

Section 11: TOXICOLOGY INFORMATION

EFFECTS OF ACUTE EXPOSURE

Component Analysis

Ingredient	LD₅₀ (oral)	LC₅₀
Acetone	5800 mg/kg, rat	Not available.
Toluene	636 mg/kg, rat	8000 mg/m ³ , rat
Isobutane	Not available.	Not available.
Ethylene glycol monobutyl ether	470 mg/kg, rat	450 ppm 4 hrs, rat
Methyl ethyl ketone	2737 mg/kg, rat	23500 mg/m ³ 8hrs, rat
Propane	Not available.	Not available.

Eye: May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.

Skin: May cause skin irritation. Handling can cause dry skin.

Ingestion: Not a normal route of exposure. Harmful: may cause lung damage if swallowed.

Inhalation: Harmful by inhalation. May cause respiratory tract irritation. May cause asphyxiation. This product may be aspirated into the lungs and cause chemical pneumonitis. Vapours may cause drowsiness and dizziness.

MATERIAL SAFETY DATA SHEET

Misty Vandalism Mark Remover

EFFECTS OF CHRONIC EXPOSURE

Target Organs: Not available.

Chronic Effects: (Effects due to excessive exposure to the raw materials of this mixture) May cause cardiac abnormalities, kidney and/or lung damage. Lab animals have experienced anemia, kidney, liver, lung and blood damage due to Ethylene glycol monobutyl ether.

Carcinogenicity: Not hazardous by WHMIS/OSHA criteria.

Ingredient	Chemical Listed as Carcinogen or Potential Carcinogen *
Acetone	Not listed.
Toluene	Not listed.
Isobutane	Not listed.
Ethylene glycol monobutyl ether	Not listed.
Methyl ethyl ketone	Not listed.
Propane	Not listed.

* See Section 15 for more information.

Mutagenicity: Not hazardous by WHMIS/OSHA criteria.

Reproductive Effects: Not hazardous by WHMIS/OSHA criteria.

Developmental Effects:

Teratogenicity: Hazardous by WHMIS/OSHA criteria.

Embryotoxicity: Hazardous by WHMIS/OSHA criteria.

Respiratory Sensitization: Not hazardous by WHMIS/OSHA criteria.

Skin Sensitization: Not hazardous by WHMIS/OSHA criteria.

Toxicologically Synergistic Materials: Not available.

Section 12: ECOLOGICAL INFORMATION

Ecotoxicity: May cause long-term adverse effects in the aquatic environment

Persistence / Degradability: Not available.

Bioaccumulation / Accumulation: Not available.

Mobility in Environment: Not available.

Section 13: DISPOSAL CONSIDERATIONS

Disposal Instructions:

This material must be disposed of in accordance with all local, state, provincial, and federal regulations.

Section 14: TRANSPORTATION INFORMATION

DOT Classification

ORM-D

TDG Classification

Limited Quantity

MATERIAL SAFETY DATA SHEET

Misty Vandalism Mark Remover

Section 15: REGULATORY INFORMATION

Federal Regulations

Canadian: This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

US: MSDS prepared pursuant to the Hazard Communication Standard (29 CFR 1910.1200).

SARA Title III

Ingredient	Section 302 (EHS) TPQ (lbs.)	Section 304 EHS RQ (lbs.)	CERCLA RQ (lbs.)	Section 313
Acetone	Not listed.	Not listed.	5,000	Not listed.
Toluene	Not listed.	Not listed.	1,000	313
Isobutane	Not listed.	Not listed.	Not listed.	Not listed.
Ethylene glycol monobutyl ether	Not listed.	Not listed.	Not listed.	Yes.
Methyl ethyl ketone	Not listed.	Not listed.	5,000	313
Propane	Not listed.	Not listed.	Not listed.	Not listed.

State Regulations

California Proposition 65:

This product contains a chemical known to the state of California to cause cancer. This product contains a chemical known to the state of California to cause birth defects or other reproductive harm.

Global Inventories

Ingredient	Canada DSL/NDSL	USA TSCA
Acetone	DSL	Yes.
Toluene	DSL	Yes.
Isobutane	DSL	Yes.
Ethylene glycol monobutyl ether	DSL	Yes.
Methyl ethyl ketone	DSL	Yes.
Propane	DSL	Yes.

HMIS - Hazardous Materials Identification System

Health - 2 Flammability - 3 Physical Hazard - 0 PPE - B

NFPA - National Fire Protection Association:

Health - 2 Fire - 3 Reactivity - 0

Hazard Rating: 0 = minimal, 1 = slight, 2 = moderate, 3 = severe, 4 = extreme

WHMIS Classification(s):

- Class A - Compressed Gas
- Class B5 - Flammable Aerosol
- Class D2A - Teratogenicity and Embryotoxicity
- Class D2B - Skin/Eye Irritant

MATERIAL SAFETY DATA SHEET

Misty Vandalism Mark Remover

WHMIS Hazard Symbols:



SOURCE AGENCY CARCINOGEN CLASSIFICATIONS:

OSHA (O) Occupational Safety and Health Administration.

ACGIH (G) American Conference of Governmental Industrial Hygienists.

A1 - Confirmed human carcinogen.

A2 - Suspected human carcinogen.

A3 - Animal carcinogen.

A4 - Not classifiable as a human carcinogen.

A5 - Not suspected as a human carcinogen.

IARC (I) International Agency for Research on Cancer.

1 - The agent (mixture) is carcinogenic to humans.

2A - The agent (mixture) is probably carcinogenic to humans; there is limited evidence of carcinogenicity in humans and sufficient evidence of carcinogenicity in experimental animals.

2B - The agent (mixture) is possibly carcinogenic to humans; there is limited evidence of carcinogenicity in humans in the absence of sufficient evidence of carcinogenicity in experimental animals.

3 - The agent (mixture, exposure circumstance) is not classifiable as to its carcinogenicity to humans.

4 - The agent (mixture, exposure circumstance) is probably not carcinogenic to humans.

NTP (N) National Toxicology Program.

1 - Known to be carcinogens.

2 - Reasonably anticipated to be carcinogens.

Section 16: OTHER INFORMATION

Disclaimer:

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.

Expiry Date: November 12, 2010

Prepared by: Nexreg Compliance Inc.

Prepared for: Amrep, Inc.

Phone: (770) 422-2071 (Mon - Fri / 8am - 5pm ET)