



# Safety Data Sheet

This safety data sheet was created pursuant to the requirements of:  
US OSHA Hazard Communication Standard (29 CFR 1910.1200)

Issue date 10-Sep-2025

Version 5

## 1. Identification of the Substance/Preparation and of the Company/Undertaking

### Product Identifier

Product name **CHAMPION SPRAYON OVEN CLEANER**  
Chemical name 7-7603-1

### Other means of identification

Product code FG 438-5177-4  
Synonyms Oven and grill cleaner

### Recommended use of the chemical and restrictions on use

Recommended Use Stoves, ovens and grills.  
Uses advised against **DO NOT USE ON FLOORS** Do not use on tile, plastic, leather, copper, painted and varnished surfaces.

### Details of the supplier of the safety data sheet

<b>Supplier Address</b>	<b>Manufacturer Address</b>
Chase Products Co.	Chase Products Co.
2727 Gardner Road	2727 Gardner Road
Broadview, IL 60155	Broadview, IL 60155
708-865-1000	708-865-1000

### Emergency Telephone Number

Company Phone Number 708-865-1000  
24 Hour Emergency Phone Number 1-800-255-3924  
Emergency telephone ChemTel 1-800-255-3924

## 2. Hazards Identification

### Classification

Skin corrosion/irritation	Category 1 Sub-category B
Serious eye damage/eye irritation	Category 2A
Gases Under Pressure	liquefied gas

### Label Elements

#### EMERGENCY OVERVIEW

**DANGER**

#### hazard statements

Causes severe skin burns and eye damage  
Causes serious eye irritation  
Contains gas under pressure; may explode if heated



# FG 438-5177-4 CHAMPION SPRAYON OVEN CLEANER

**Appearance** Yellowish, viscous liquid      **Physical State** Aerosol      **Odor** Strong, characteristic odor

## Precautionary Statements - Prevention

Do not breathe fumes, mist, vapors or spray.  
Wash face, hands and any exposed skin thoroughly after handling  
Wear protective gloves, protective clothing, eye protection and face protection.

## Precautionary Statements - Response

Specific measures. See additional cautionary statements on this label.  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
Immediately call a POISON CENTER or doctor  
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower  
Wash contaminated clothing before reuse  
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing  
Immediately call a POISON CENTER or doctor  
IF SWALLOWED: rinse mouth. Do NOT induce vomiting

## Precautionary Statements - Storage

Store locked up  
Protect from sunlight. Store in a well-ventilated place

## Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

## Hazards not otherwise classified (HNOC)

### Other Information

- Toxic to aquatic life with long lasting effects
- Toxic to aquatic life

-

## 3. Composition/information on Ingredients

**Common Name** Oven and grill cleaner.  
**Synonyms** Oven and grill cleaner.  
**Chemical Family** MIXTURES.  
**Formula** 7-7603-1  
**Chemical nature** Aqueous alkaline solution.

Chemical name	CAS No	weight-%	Trade secret
Water	7732-18-5	80-85	*
Triethylene Glycol	112-27-6	1-5	*
N-Butane	106-97-8	1-5	*
Sodium hydroxide	1310-73-2	1-5	*
Potassium hydroxide	1310-58-3	1-5	*
Propane	74-98-6	1-5	*

Chemical Additions Hazardous components according to OSHA, are listed when present at 1% or greater. Carcinogenes are listed when present at 0.1% or greater.

\* The exact percentage (concentration) of composition has been withheld as a trade secret.

## 4. First aid measures

### FIRST AID MEASURES

**Eye Contact** Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control center or doctor for treatment advice.

<b>Skin contact</b>	Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Call a poison control center or doctor for treatment advise.
<b>Inhalation</b>	If overcome by vapor, move person to fresh air. If person is not breathing, call 911 or an ambulance, then provide artificial respiration, preferably mouth-to-mouth, if possible. Call a poison control center or doctor for further treatment advise.
<b>Ingestion</b>	Call a poison control center or doctor for treatment advice. Have person sip a glass of water if able to swallow. Do not induce vomiting unless told to do so by a poison control center or doctor. Do not give anything by mouth to an unconscious person.

**Most important symptoms and effects, both acute and delayed**

<b>Symptoms</b>	Acute: Danger - contains sodium hydroxide. Injurious if sprayed on yes. Contact with eyes may result on eye damage. Irritant to skin. Prolonged contact with skin may cause severe burns. Inhalation of vapor or mist may cause headaches, dizziness and nausea. Vapors may irritate the upper-respiratory tract system.
-----------------	--

**Indication of any immediate medical attention and special treatment needed**

<b>Note to physicians</b>	None needed.
---------------------------	--------------

**5. Fire-fighting measures**

**Suitable extinguishing media**

Dry chemical, CO2 or water spray.

**Unsuitable extinguishing media** Caution: Use of water spray when fighting fire may be inefficient.

**Specific hazards arising from the chemical**

This product is under pressure. Water spray may be used to cool cans in the vicinity of fire or excessive heat to prevent the explosion of the cans.

**Hazardous combustion products** Thermal decomposition may release carbon monoxide and carbon dioxide.

**Explosion data**

**Sensitivity to Mechanical Impact** Contents under pressure, keep away from heat and open flame.

**Sensitivity to Static Discharge** Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity).

**Protective equipment and precautions for firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

**6. Accidental release measures**

**Personal precautions, protective equipment and emergency procedures**

**Personal precautions** Use with adequate general or local exhaust ventilation.

**For emergency responders** Remove all sources of ignition.

**Environmental precautions**

**Environmental precautions** See Section 12 for additional Ecological Information.

**Methods and material for containment and cleaning up**

**Methods for Containment** Provide adequate ventilation to area being treated. Soak up spills with chemically inert,

absorbent material.

**Methods for cleaning up** Clean contaminated surface thoroughly.

**7. Handling and Storage**

**Precautions for safe handling**

**Advice on safe handling** Avoid contact with skin. Avoid getting spray into eyes. Do not deliberately inhale vapor or mist. Do not contaminate food or food handling surfaces. Keep out of reach of children.

**Conditions for safe storage, including any incompatibilities**

**Storage Conditions** Store in a cool, dry place away from heat and open flame. Keep out of reach of children. **AEROSOL STORAGE LEVEL I (NFPA-30B) .**

**Incompatible Materials** Avoid heat, open flame and contact with strong oxidizers. Avoid contact with tile, plastic, leather, copper, painted and varnished surfaces.

**8. Exposure Controls/Personal Protection**

**Control parameters**

**Exposure guidelines** See occupational exposure limits listed below.

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
N-Butane 106-97-8	STEL: 1000 ppm explosion hazard	(vacated) TWA: 800 ppm (vacated) TWA: 1900 mg/m <sup>3</sup>	IDLH: 1600 ppm TWA: 800 ppm TWA: 1900 mg/m <sup>3</sup>
Sodium hydroxide 1310-73-2	Ceiling: 2 mg/m <sup>3</sup>	TWA: 2 mg/m <sup>3</sup> (vacated) Ceiling: 2 mg/m <sup>3</sup>	IDLH: 10 mg/m <sup>3</sup> Ceiling: 2 mg/m <sup>3</sup>
Potassium hydroxide 1310-58-3	Ceiling: 2 mg/m <sup>3</sup>	(vacated) Ceiling: 2 mg/m <sup>3</sup>	Ceiling: 2 mg/m <sup>3</sup>
Propane 74-98-6	: See Appendix F: Minimal Oxygen Content, explosion hazard	TWA: 1000 ppm TWA: 1800 mg/m <sup>3</sup> (vacated) TWA: 1000 ppm (vacated) TWA: 1800 mg/m <sup>3</sup>	IDLH: 2100 ppm TWA: 1000 ppm TWA: 1800 mg/m <sup>3</sup>

**Appropriate engineering controls**

**Engineering controls** Use with adequate general or local exhaust ventilation.

**Individual protection measures, such as personal protective equipment**

**Eye/face Protection** Conventional eyeglasses to guard against splashing.

**Skin and Body Protection** Rubber, vinyl or household type gloves required.

**Respiratory protection** Use in well-ventilated area ONLY. When using indoors, keep windows and doors open until fumes disipate.

**General hygiene considerations** Wash hands thoroughly after handling. Wash contaminated clothing before reuse.

**9. Physical and Chemical Properties**

**Information on basic physical and chemical properties**

<b>Physical State</b>	Aerosol	<b>Odor</b>	Strong, characteristic odor
<b>Appearance</b>	Yellowish, viscous liquid	<b>Odor threshold</b>	No information available
<b>Color</b>	light yellow		



Thermal decomposition may yield gases like carbon monoxide and carbon dioxide.

**11. Toxicological Information**

**Information on likely routes of exposure**

<b>Product Information</b>	Danger contains Sodium Hydroxide
<b>Inhalation</b>	Vapors may irritate the upper-respiratory tract system. Inhalation of vapor or mist may cause headaches, dizziness and nausea.
<b>Eye Contact</b>	Injurious if sprayed on eyes. Contact with eyes may result on eye damage.
<b>Skin contact</b>	Danger, contains sodium hydroxide. Irritant to skin. Prolonged contact with skin may cause severe burns.
<b>Ingestion</b>	This is an aerosol product, ingestion is unlikely to occur. MAY BE HARMFUL IF SWALLOWED.

Chemical name	Oral LD50	dermal LD50	Inhalation LC50
Water 7732-18-5	> 90 mL/kg ( Rat )	-	-
Triethylene Glycol 112-27-6	= 17 g/kg ( Rat )	> 20 mL/kg ( Rabbit )	> 5.2 mg/L ( Rat ) 4 h
N-Butane 106-97-8	-	-	= 658 g/m <sup>3</sup> ( Rat ) 4 h
Sodium hydroxide 1310-73-2	= 325 mg/kg ( Rat )	= 1350 mg/kg ( Rabbit )	-
Potassium hydroxide 1310-58-3	= 284 mg/kg ( Rat )	-	-
Propane 74-98-6	-	-	> 800000 ppm ( Rat ) 15 min

**Information on toxicological effects**

**Symptoms** Vapors may be irritating to eyes, nose, throat, and lungs.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Skin corrosion/irritation** May cause severe burns after prolonged contact with skin.  
**Serious eye damage/eye irritation** Risk of serious damage to eyes.  
**corrosivity** Contains sodium hydroxide, can be corrosive to skin and eyes.  
**sensitization** No information available.  
**Germ cell mutagenicity** No information available.  
**Carcinogenicity** Not known chronic effects based on available data. None of the ingredients present in excess of 0.1% are listed as carcinogenic by NTP, IARC or OSHA.

**Reproductive toxicity** No information available.  
**STOT - single exposure** No information available.  
**STOT - repeated exposure** No information available.  
**Aspiration Hazard** Deliberate inhalation of concentrated vapor or mist may cause headache, dizziness and nausea.

**Numerical measures of toxicity - Product Information**

**Unknown acute toxicity** -  
**The following values are calculated based on chapter 3.1 of the GHS document**  
**ATEmix (oral)** 17749 mg/kg  
**ATEmix (dermal)** 46056 mg/kg  
**ATEmix (inhalation-gas)** 8757000 mg/l

ATEmix (inhalation-dust/mist) 46.1 mg/l  
 ATEmix (inhalation-vapor) 14403 mg/l

**12. Ecological Information**

**ecotoxicity**

See information listed below.

Chemical name	Algae/aquatic plants	Fish	Toxicity to Microorganisms	Crustacea
Triethylene Glycol 112-27-6		56200 - 63700: 96 h Pimephales promelas mg/L LC50 flow-through 10000: 96 h Lepomis macrochirus mg/L LC50 static 61000: 96 h Lepomis macrochirus mg/L LC50 flow-through		42426: 48 h Daphnia magna mg/L EC50
Sodium hydroxide 1310-73-2		45.4: 96 h Oncorhynchus mykiss mg/L LC50 static		

**Persistence and degradability**

No information available.

**Bioaccumulation**

No information available.

Chemical name	Partition coefficient
Triethylene Glycol 112-27-6	-1.98
N-Butane 106-97-8	2.31
Potassium hydroxide 1310-58-3	0.65 0.83
Propane 74-98-6	1.09

**Other adverse effects**

No information available

**13. Disposal Considerations**

**Waste treatment methods**

**Disposal of wastes**

Dispose of in accordance with federal, state and local regulations.

**Contaminated packaging**

Pressurized container: Do not pierce or burn, even after use. Do not puncture or incinerate container. If empty: Place in trash or offer for recycling if available. If partly filled: Call your local solid waste agency for disposal instructions.

Chemical name	California Hazardous Waste Status
Sodium hydroxide 1310-73-2	Toxic Corrosive
Potassium hydroxide 1310-58-3	Toxic Corrosive

**14. Transport Information**

**DOT**

**UN/ID no** Limited Quantity  
**Proper Shipping Name** Consumer Commodity  
**Hazard Class** NA

**IATA**

**UN/ID no** UN1950  
**Proper Shipping Name** Aerosols, non-flammable, containing substances in Class 8 packing group II  
**Hazard Class** 2.2 (8)

**IMDG**

**UN/ID no** UN1950  
**Proper Shipping Name** Aerosols, non-flammable  
**Hazard Class** 2.2 (8)

**15. Regulatory information**

**International Inventories**

**TSCA** All ingredients of this product are listed or are excluded from listing under the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.  
**DSL** All ingredients are listed or are excluded from listing on the DSL.

**Legend:**

TSCA - *United States Toxic Substances Control Act Section 8(b) Inventory*  
 DSL/NDSL - *Canadian Domestic Substances List/Non-Domestic Substances List*

**US Federal Regulations**

**SARA 313**

This product does not contain toxic chemicals (above the de minimis level) subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 and of 40 CFR 372.

**SARA 311/312 Hazard Categories**

**Acute Health Hazard** yes  
**Chronic Health Hazard** No  
**Fire Hazard** No  
**Sudden release of pressure hazard** No  
**Reactive Hazard** No

**CWA (Clean Water Act)**

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Sodium hydroxide 1310-73-2	1000 lb			X
Potassium hydroxide 1310-58-3	1000 lb			X

**CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
---------------	--------------------------	----------------	--------------------------

**FG 438-5177-4 CHAMPION SPRAYON OVEN CLEANER**

Sodium hydroxide 1310-73-2	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ
Potassium hydroxide 1310-58-3	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ

**US State Regulations**

**California Proposition 65**

This product does not contain any Proposition 65 chemicals

**U.S. State Right-to-Know Regulations**

Chemical name	New Jersey	Massachusetts	Pennsylvania
Water 7732-18-5			X
Triethylene Glycol 112-27-6			X
N-Butane 106-97-8	X	X	X
Sodium hydroxide 1310-73-2	X	X	X
Potassium hydroxide 1310-58-3	X	X	X
Propane 74-98-6	X	X	X

**U.S. EPA Label information**

**EPA Pesticide registration number** Not applicable

**16. Other information**

<b><u>NFPA</u></b>	<b>Health Hazards</b> 3	<b>Flammability</b> 1	<b>Instability</b> 1	<b>Physical and chemical properties</b> Not applicable <b>Personal Protection</b> B - Eyes and hands protection
<b><u>HMIS</u></b>	<b>Health Hazards</b> 3	<b>Flammability</b> 2	<b>Physical hazards</b> 1	

**Prepared by** Regulatory Department  
**Issue date** 10-Sep-2025  
**Revision note**  
**This SDS supersedes a previous SDS dated:** 12-Sep-2024

**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**