



## LGR 2800i

### High Temperature Performance Winner

The LGR 2800i refrigerant dehumidifier offers exceptional performance across the full range of jobsite conditions – in low humidity environments and even at high temperatures (up to 125°F). The unit is engineered for the heavy demands of water damage restoration and rental use. A rugged rotomolded housing and durable construction make this Dri-Eaz dehumidifier a top choice for professionals everywhere.

The LGR 2800i provides high performance with low energy consumption - 130 pints per day (at AHAM) with just 8 amps, as verified by a laboratory under contract to AHAM.

### Product Features

- Built-in thermo-hygrometer monitors and displays inlet and outlet conditions.
- Automatic humidistat control.
- Automatic high temperature mode – no manual adjustments required.
- Outstanding performance at only 8 amps.
- HygroTrac-ready – track dehumidifier performance automatically on the HygroTrac website
- Legendary Dri-Eaz rotomolded housing resists dents and scratches – and is easy to keep looking new.
- If power is interrupted during operation, the unit will automatically restart when power is restored. (115V models only.)



Item #F410  
\$2,780 Suggested List U.S. Funds

### Product Specifications

|                                  |  |
|----------------------------------|--|
| Model                            | LGR 2800i – F410                                     |
| Power                            | 8 amps, 115 volts                                    |
| Water removal AHAM (80°F/60% RH) | 130 pints   61.5 liters / day                        |
| Water removal max. (90°F/90% RH) | 200 pts.   94.6 liters / day                         |
| Water removal min. (80°F/20% RH) | 20 pts.   9.5 liters / day                           |
| Max. process air                 | 400 CFM   679.7 CMH*                                 |
| Air filter                       | 3M HAF filter (Dri-Eaz part no. F421)                |
| Dimensions (H x D x W)           | 40.5 x 23 x 24 in.<br>103 x 58 x 61 cm               |
| Use weight                       | 160 lbs.   72.6 kg                                   |
| Power cord                       | 25 ft.   7.6 m detachable                            |
| Hose                             | 40 ft.   12.2 m                                      |
| Construction                     | Rotomolded polyethylene shell                        |
| Safety                           | ETL certified to UL 474 and CSA 22.2 no. 92          |
|                                  | *Automatic variable speed for optimized performance. |