

### TRANSFORMING AIR PURIFICATION



## inactivates indoor pathogens.

EEKS, CAPTURES AND

CHANGE IS IN THE AIR.

### Greentech 750+ wall mount Active Air Purifier with PCO & ODOGard® Technology

### What's in the Plus?

Only Greentech has the filters with the plus. Our MERV-rated pleated filters treated with ODOGard® coating traps and inactivates pathogens and allergens. ODOGard instantly bonds to odor molecules and changes their molecular structure, completely clearing rooms of odors in under 10 minutes.

### Applications::

Workshops • Offices • Schools Day Care Facilities • Nursing Homes • Nail Salons • Veterinary Clinics • Motor Coaches Public Restrooms

#### Features:

- Active Air Purification
- No Ductwork Required
- Easily Mounts to Wall
- 24/7 Odor and Particulate Reduction
- Replaceable PCO Cell and MERV+ Filter

UnoClean.com (224) 654-6500

## Benefits of Greentech's 750+ Wall Mount



Continuous Purification



Sized for Multiple Locations



Reduces Odors



Mounts to Save Space



Wide List of Applications

# Active Oxidation Improves Air Quality



Providing continuous air purification, this permanently mounted unit is perfect for spaces without HVAC duct access. Greentech's 750+ Wall Mount features the same active air purification technology developed and used by NASA.



ODO Gard

AOPs are propelled out into your space to hunt down particulates, even the very small ones. At the same time, negative ions go out and charge particles such as dust, pollen and pet dander, causing them to drop out of your breathing space.

Our MERV+ filters have an ODOGard® coating

that eliminates odors at the molecular level,

making it impossible for the odor to survive.

odors don't stand a chance against ODOGard.

Even the toughest, seemingly permanent



Photocatalytic oxidation (PCO) technology uses energy to activate a catalyst, turning moisture into products that continuously clean your space.

## Features and Specifications

### UNIT

- Models: Greentech SIREN 750+ Wall Mount 1X5789 Greentech 750+ Wall Mount NO3 (no ozone) 1X5821
- Dimensions: 11.92" H x 9.72" W x 3.64" D
- Metric: 303mm H x 247mm W x 93mm D
- Weight: 3.3lbs (1.5kg)
- Materials: Powder Coated Aluminum
- Unit Warranty: 2 Year Manufacturer's Warranty

### PERFORMANCE

- Airflow: 70 CFM
- Optional Ozone Output: < 0.05 ppm
- Coverage: up to 750 ft<sup>2</sup>

### POWER

- Input Voltage: 24VDC
- Operating Voltage 24VDC
- Supply Power: 120-240VAC | 17W
- Operating Power: 24VDC | .67A

### **TECHNOLOGIES**

- PCO: Photocatalytic Oxidation
- ODOGard® Coated MERV+ Filter
- Bipolar Ionization Module (BPI)
- Activated Oxygen (Ozone) Optional

## To Use This Product Correctly

Read All Instructions Carefully in User Manual Before Operating Purifier.

REV 220818