



Base 16

Floor Sealer

Base 16 is a water emulsion sealer for use on vinyl, resilient tile, linoleum, terrazzo, rubberized, and other porous or worn floors. Base 16 fills pores and provide an optimal base for any water-based polymer floor finish. Excellent base for any floor maintenance program including high speed and propane. Enhances the gloss and improves the appearance, durability and performance of any floor finish. It will also extend the time between strip outs thereby reducing the cost of maintenance. Easily applied with a mop or applicator system. Dries quickly for rapid recoating.

DIRECTIONS

Read the entire label and SDS for proper use, handling and storage before using this product.

Application: For best results, floors should be bare, fully stripped of all previous coatings, and then neutralized.

1. Apply coats of sealer in full uniform coats.
2. Allow to dry before applying additional coats of sealer.
3. For maximum performance, apply 1-2 additional coats of sealer until the floor has a smooth even appearance. The floor is now sealed and ready for the application of floor finish.

Stripping: This sealer can be removed using a high quality Nyco stripping solution.



FAST FACTS

- Provides base coat for any emulsion coating
- Fills and smooths pores in flooring
- Improves appearance and durability of any floor finish
- Removable

MARKETS

- Building Service Contractors
- Retail
- Education
- Healthcare
- Hospitality & Lodging

SPECIFICATIONS

Color	Opaque White
Scent	Acrylic
pH	8.0 - 8.8
Solid Content	16%

Slip Resistance is greater than 0.5% coefficient of friction. Meets or exceeds ASTM D-2047.

PACKAGING

NL140-G4	4x1 Gallons/Case
NL140-P5	5 Gallon Pail
NL140-D30	30 Gallon Drum
NL140-D55	55 Gallon Drum