



Ure-Coat

Urethane Fortified Seal & Finish

Ure-Coat is a water-based polymer coating fortified with urethane for superior performance and appearance. Extremely durable on any floor including terrazzo, quarry tile, brick, and concrete. Deep gloss, brilliance, and extended wear on resilient floors in high traffic areas. Ideal for entrances, hallways, and classrooms. Fast, odorless coating for protection, appearance, and dust control in light duty warehouse and industrial settings. Superior performance and durability reduces maintenance costs and the need for frequent stripping and recoating in heavily used areas.

DIRECTIONS

Read the entire label and SDS for proper use, handling and storage before using this product.

Application: For best results, floors should be clean and/or old coatings removed and the floor neutralized.

1. Apply finish in full uniform coats.
2. Allow to dry before recoating.
3. For maximum performance, apply additional coats of finish until the desired level of appearance and protection is achieved.
4. Allow to dry thoroughly before reopening up area for traffic.

Buffing: This finish can be spray buffed or high speed buffed. Follow directions of buffing compound.

Stripping: This finish can be removed using a high quality Nyco stripping solution.



FAST FACTS

- Urethane fortified for extended durability
- Use in high traffic conditions
- Ideal for use on terrazzo, resilient, and concrete floors
- Use with any buffing/burnishing and floor maintenance program
- Resists marking and penetration of dirt and soils
- Easily applied with a mop or applicator system

MARKETS

- Building Service Contractors
- Retail
- Education
- Healthcare
- Hospitality & Lodging

SPECIFICATIONS

Color	Opaque White
Scent	Acrylic
pH	8.0 - 9.0
Solid Content	22%

Slip Resistance is greater than 0.5% coefficient of friction. Meets or exceeds ASTM D-2047.

PACKAGING

NL154-G4	4x1 Gallons/Case
NL154-P5	5 Gallon Pail
NL154-D30	30 Gallon Drum
NL154-D55	55 Gallon Drum