



Pro-Ultra 22

Ultra High Speed Floor Finish

Pro-Ultra 22 is a high performance acrylic floor finish specifically designed for use all floor high speed buffing and burnishing programs. Pro-Ultra 22 is ideal for frequent burnishing programs and is optimized for the speed and pad pressure of propane machines. It will provide a long-lasting mark resistant finish with a brilliant deep gloss. Use on resilient tile, terrazzo, and other floors that are frequently buffed and burnished. Easy to apply, dries quickly for rapid recoating. Superior durability, gloss, and mark resistance.

DIRECTIONS

Read the entire label and SDS for proper use, handling and storage before using this product.

Application: For best results, floors should be clean and/or old coatings removed and the floor neutralized.

1. Apply finish in full uniform coats.
2. Allow to dry before recoating.
3. For maximum performance, apply additional coats of finish until the desired level of appearance and protection is achieved.
4. Allow to dry thoroughly for several hours before reopening up area for traffic.

Buffing: This finish can be repeatedly high speed buffed/burnished. Allow to dry thoroughly before buffing.

Stripping: This finish can be removed using a high quality Nyco stripping solution.



FAST FACTS

- Brilliant gloss
- Optimized for frequent burnishing programs
- Mark resistant
- Durable
- Fast dry and recoat cycle

MARKETS

- Building Service Contractors
- Retail
- Education
- Healthcare
- Hospitality & Lodging

SPECIFICATIONS

| | |
|----------------------|--------------|
| Color | Opaque White |
| Scent | Acrylic |
| pH | 8.0 - 9.0 |
| Solid Content | 22% |

Slip Resistance is greater than 0.5% coefficient of friction. Meets or exceeds ASTM D-2047.

PACKAGING

| | |
|------------------|------------------|
| NL175-G4 | 4x1 Gallons/Case |
| NL175-P5 | 5 Gallon Pail |
| NL175-D30 | 30 Gallon Drum |
| NL175-D55 | 55 Gallon Drum |