



***R&B Wire Products, Inc.***

## **ASSEMBLY INSTRUCTIONS**

### **ELEVATED BUSHEL TRUCK**

Tools required will be a standard screwdriver and a 7/16" wrench.

#### **BUSHEL TRUCK**


- 1) Remove base and basket or tub from carton and place the basket or tub on top of the base.



- 2) Push back the liner so that the holes in the base and the basket are visible.



- 3) Insert the bolt through the basket frame and base until the bolt is visible past the base tube.



- 4) Take the nut and place onto the bolt. Finger tighten only.



- 5) Repeat these steps on the other 3 bolts until all four have been installed. Tighten all four nuts and bolts until secure. Your Elevated Bushel Cart is now ready for use.

#### **WARNING**

- Never allow children (or adults) to ride in or on the cart.
- Always proceed slowly. Be sure wheels roll free and turn easily.
- Place all loads in the center of the basket or tub for balance.
- Maximum capacity: 463 (3 bu) – 40 lbs; 464 (4 bu) – 50 lbs; 466 & 4606 (6 bu) – 60 lbs.



To Purchase - [www.UNOCLEAN.com](http://www.UNOCLEAN.com)

phone: 888-226-2724



"YOUR RELIABLE PARTNER  
FOR OVER 57 YEARS"