



Hytron®

Heavy-Duty Chlorinated Dishwasher Detergent For Mechanical Dishwashers



Hytron®
ST-708, 84 x 1 oz. pack

ST-No.	UPC No. Mfg. No. 071206	Case Size	Case Weight	Cases/Pallet
ST-708	007087	84 x 1 wt. oz. pack	6.5 pounds	154
ST-705	007056	200 x 1 wt. oz. pack	15.75 pounds	60

This product is also available in bulk sizes.

Personal Protective Equipment: 1. Wear protective gloves.
2. Wear protective eyewear.



Unused Product Disposal: Unused product or its solutions may be poured down the drain. Never pour unused product or its solutions down an outdoor drain.

Improper dilution or improper use of this product may result in skin and eye irritation, damage to surfaces and unsatisfactory cleaning performance.

Pack Recycling: Empty packs should be rinsed out with cold water and then placed for recycling where accepted.

FOODSERVICE

Hytron® is a hard working, caustic-free, fully active detergent for use in institutional mechanical dishwashers. Ideal size for guests' use in resort rentals.

Hytron® emulsifies grease by keeping it in dynamic suspension. It also de-stains dishes (including plasticware). It assures clean and sparkling dishes, glassware, and silverware.

When used as directed, Hytron® keeps dishes, glassware, and silverware free from spots and water marks.

Directions

Empty contents of pack into detergent dispenser compartments. Run machine as usual. Use 1 pack per 3 gallons of water.

Chemical Characteristics

Abrasive.....	no
Appearance.....	white powder
Biodegradable.....	yes
Corrosive	no
Fragrance	chlorine scent
Non-Flammable	yes
NSF Certified.....	A1
pH (1% Solution).....	10.5
Phosphate-free	no

Ingredients

The ingredients in Hytron® are sodium metasilicate anhydrous, sodium sulfate, sodium carbonate, sodium tripolyphosphates, sodium dichloroisocyanurate, and a rinse additive.



MATERIAL SAFETY DATA SHEET

SECTION 1 – PRODUCT/MANUFACTURER'S IDENTITY

Product Name: Hytron®
Synonyms: ST-705, ST-708
Chlorinated Hytron-Low Phosphorus
Hytron Automatic Dishwasher Det.
Company: Stearns Packaging Corporation
4200 Sycamore Avenue (53714)
PO Box 3216
Madison, WI 53704-0216
Phone: 800-655-5008
Fax: 608-246-5149
Website: www.stearnspkg.com

Formula ID Number: DP10
MSDS File Name: HYTRON
EPA Reg #: None
DOT Hazard Class: None
DOT Shipping Name: Cleaning Compounds, NOI,
powder. Item 48581, Class 55
NSF Certified: A1, 7/20/04

Concentrate		In Dilution		HAZARD RATING
0	Flammability	0	0	
2	Health	1	1	
0	Reactivity	0	0	
None	Special Hazard	None	None	

4 = Extreme
3 = High
2 = Moderate
1 = Slight
0 = Insignificant

Emergency Contact: CHEM-TEL, 800-255-3924

Abbreviation Key: N.A.=Not Applicable,
N.D.=Not Determined

SECTION 2 – HAZARDOUS INGREDIENTS / IDENTITY INFORMATION

CHEMICAL IDENTIFICATION	CAS NO.	HAZARD	OSHA PEL(ppm)	ACGIH TLV(ppm)	%(Optional)
Sodium carbonate	497-19-8	Irritant			10 - 30
Sodium metasilicate	6834-92-0	Corrosive	15 mg/m3	10 mg/m3	5 - 7
Silicic acid, sodium salt	1344-09-8	Irritant			5 - 7
Sodium tripolyphosphate	7758-29-4	Irritant			< 2
Sodium dichloro-S-triazinetrione dehydrate	51580-86-0	Corrosive/Oxidizer		*	< 1

* TLV for chlorine is 0.5 ppm (1.5 mg/m3) TWA and 1 ppm STEL

SARA Section 313 Title III Notification Required: No

SECTION 3 – PHYSICAL DATA

Appearance and Odor: White granules and crystals, chlorine odor
Solubility in water: Complete
Boiling Point: N.D.
Melting Point: N.A.
Vapor Pressure (mm Hg): N.D.
Vapor Density (Air=1): N.D.
Evaporation Rate (Water=0.3): N.D.
pH (Concentrate): N.D.
pH (1% Solution): 10.5
Specific Gravity: N.A.

SECTION 4 – FIRE AND EXPLOSION HAZARD DATA

Flash Point and Method: Non-combustible, >200°F
Special Fire Fighting Procedures: Use full protective clothing and self-contained breathing apparatus.
Flammable Limits: LEL: N.A.
UEL: N.A.
Extinguishing Media: N.A.
Unusual Fire & Explosion Hazards: None

SECTION 5 – REACTIVITY DATA

Chemical Stability: Stable: Unstable:
Conditions to Avoid: Under freezing and extremes of heat.
Incompatibility (Materials to Avoid): Avoid contact with easily oxidizable organic materials. Also avoid ammonia, urea, or similar nitrogen-containing compounds, inorganic reducing compounds, floor sweeping compounds, calcium hypochlorite, alkalis.
Hazardous Polymerization: May Occur Will Not Occur
Hazardous Decomposition or By-Products: Chlorine-containing gases can be produced.

SECTION 6 – HEALTH HAZARD DATA/FIRST AID PROCEDURES

Health Hazards (Acute and Chronic): Strongly alkaline; may cause burning to eyes and respiratory passages. Possible irritant to skin over prolonged periods of exposure.
Signs and Symptoms of Exposure: Irritation of exposed tissues, especially eyes, skin, throat, nasal cavities, and other mucous membranes.
Emergency and First Aid Procedures:
Eyes: Flush with cool water for at least 15 minutes. If irritation persists, consult a physician.
Skin: May be irritating to skin. Flush with water and wear gloves in the future to minimize exposure. Wash hands thoroughly after handling. Discontinue use if irritation persists and consult a physician.
Inhalation: Remove from exposure. Obtain medical attention immediately.
Ingestion: May be harmful if swallowed. Drink large amounts of water or milk. **DO NOT** induce vomiting. Get medical attention immediately. Avoid contamination of foods.
Medical Conditions Aggravated by Exposure: No data available
Carcinogenicity: IARC Monographs? Yes No
NTP? Yes No OSHA Regulated? Yes No

NOTE TO PHYSICIAN: Strongly alkaline, may remove sebaceous oils leaving skin unprotected and may cause chemical burns. Accessible exposed tissue should be flushed thoroughly with water, and any corneal burns warrant consultation of an ophthalmologist. Ingestion may result in nausea, vomiting and burns, especially of the esophagus. Attempts to neutralize ingested material with acids may cause excess heat and gas production, which can increase the risk of perforation. Dilution may so likewise, but when the dry material is ingested, adherence of the particles to the esophageal mucosa may assure perforation and/or stricture formation may occur without oropharyngeal burns. Accordingly, most authorities recommend limited esophageal stenosis. Prevention of the latter is controversial, though most authorities favor early corticosteroid and/or prophylactic dilation therapy.

SECTION 7 – PREVENTATIVE AND CONTROL MEASURES

Ventilation: Local Exhaust: To control below 2 mg/m3 TLV for dusts of sodium metasilicate.
Mechanical: To control below 2 mg/m3 TLV for dusts of sodium metasilicate.
Skin Protection: Use neoprene, rubber, or other chemical resistant gloves. Wear protective clothing to prevent repeated or prolonged contact.
Eye Protection: Splash goggles, or safety glasses if splashing is not a concern.
Respiratory Protection: In general, respirators are not needed if the product is used in a well-ventilated area. However, a respirator is recommended when working with products where dusts and mists cause irritation of the eyes and/or mucous membranes.
Steps to be Taken if Material is Spilled or Released: Sweep up for salvage or disposal. Take care to avoid contact with large amounts of dust.
Waste Disposal: Comply with all local, state and federal regulations. Consult your state DNR or the EPA for specific questions. Wastewater should never enter a fresh water body without treatment.
Handling and Storage: Wear all recommended safety gear. Do not mix with other chemicals or cleaning agents. Avoid contact with dust.
Other Precautions: Keep out of the reach of children.

SECTION 8 – OTHER REGULATORY INFORMATION

California Safe Drinking Water and Toxic Enforcement Act of 1986 – No chemicals listed by California are present at a level that poses a significant risk of causing cancer or reproductive toxicity.
State Right-to-Know - top five ingredients: sodium carbonate/497-19-8, sodium chloride/7647-14-5, sodium sulfate anhydrous/7757-82-6, sodium citrate/6132-04-3, sodium metasilicate anhydrous/6834-92-0.
Toxic Substances Control Act (TSCA): All the ingredients are listed on the TSCA Chemical Substance Inventory.

This MSDS data relates only to the material designated and does not relate to its use with any other material or process. The data is believed to be accurate. However, since use conditions vary and are outside our control, Stearns Packaging Corporation makes no warranties, expressed or implied, and assumes no liability for failure to follow directions and safety precautions.